



Moisture Sensor For Insulating Oil

Direct Reading: Parts per Million (ppm) Total Water in Transformer Oil

Doble DOMINO™ on-line moisture sensor detects water in insulating oil – reads directly in parts per million (ppm) of total water. Use with systems employing Velcon Filters, Inc.'s patented **Superdri**® dissolved water removal cartridges. Use of the moisture sensor eliminates the need for chemical titration samples. The moisture sensor will also indicate when to change-out the **Superdri** cartridges.

FEATURES

- Continuous measurement of moisture in oil
- Displays parts per million (ppm) of total water and also displays oil temperature
- Can also display percent saturation of oil (water activity)
- Alarm feature to indicate **Superdri** cartridge change-out needed
- Microprocessor based transmitter
- 0 - 5 volt analog output signals
- RS-232C serial bus output
- Stainless Steel filter sensor protection
- Operating voltage: 24 volts



ORDERING INFORMATION

Available as an option for the SDS20 Transformer Oil Fill System and TDS5 Transformer Dry-out System. Order Part Number 746Y005.

Call factory for retrofit kit to install on your existing SDS20 or TDS5 system.

Not for stand-alone use.



Velcon products are sold and serviced by a world-wide representative network. To order, contact Headquarters or your **LOCAL REPRESENTATIVE**:

COMPANY HEADQUARTERS:
Velcon Filters, Inc.
1210 Garden of the Gods Road
Colorado Springs, CO 80907-3410
Phone: 1.800.531.0180 / 1.719.531.5855
Fax: 719.531.5690
e-mail: vfsales@velcon.com
www.velcon.com

MANUFACTURING PLANTS LOCATED AT:
Colorado Springs, Colorado
Sylacauga, Alabama

OVERSEAS AFFILIATES:
Frankfurt/M., Germany & Singapore

*Liquid Filtration
and Separation
Specialists*

Due to Velcon Filters' continuing product improvement, drawings, specifications and pictures are subject to change without notice.